



| Pressione max di esercizio raccomandata Kg/cm ² | Grandezza | Tipo | Dimensioni | | | | | | | | | | | Viti | | Or tipo | Peso Kg |
|--|-----------|------|------------|---|---|---|---|---|---|---|---|---|---|--------|-----|---------|-----------|
| Maximum recommended working pressure Kg/cm ² | Size | Type | Dimensions | | | | | | | | | | | Screws | | Or type | Weight Kg |
| | | | A | B | C | D | E | F | G | H | I | L | S | Metric | Unc | | |

SERIE 3000

| | | | | | | | | | | | | | | | | | |
|-----|-------|------------|---------------|-------|-------|----|-------|----|----|----|-----|------|-------|--------|------------|------|------|
| 345 | 1/2" | AFS080J034 | 3/4" - 16UNF | 9,90 | 38,10 | 54 | 17,48 | 46 | 52 | 13 | 6,4 | 9 | 10,82 | M8x30 | 5/16x1"1/4 | 4075 | 0,25 |
| 345 | 1/2" | AFS080J078 | 7/8" - 14UN | 12,30 | 38,10 | 54 | 17,48 | 46 | 52 | 13 | 6,8 | 9 | 13,69 | M8x30 | 5/16x1"1/4 | 4075 | 0,30 |
| 345 | 3/4" | AFS100J | 1"1/16 - 12UN | 15,50 | 47,63 | 65 | 22,23 | 50 | 60 | 14 | 8,0 | 11,5 | 16,87 | M10x35 | 3/8x1"1/2 | 4100 | 0,36 |
| 345 | 1" | AFS102J | 1"5/16 - 12UN | 21,50 | 52,37 | 70 | 26,19 | 55 | 63 | 16 | 8,0 | 11,5 | 23,19 | M10x35 | 3/8x1"1/2 | 4131 | 0,50 |
| 276 | 1"1/4 | AFS104J | 1"5/8 - 12UN | 27,50 | 58,72 | 79 | 30,18 | 68 | 65 | 14 | 9,3 | 11,5 | 29,13 | M10x35 | 7/16x1"3/4 | 4150 | 0,71 |
| 207 | 1"1/2 | AFS106J | 1"7/8 - 12UN | 33,00 | 69,85 | 94 | 35,71 | 78 | 70 | 16 | 9,6 | 13,5 | 35,08 | M12x35 | 1/2x1"3/4 | 4187 | 1,02 |

SERIE 6000

| | | | | | | | | | | | | | | | | | |
|-----|-------|------------|---------------|-------|-------|-----|-------|----|----|----|-----|------|-------|--------|------------|------|------|
| 414 | 1/2" | AFS401J034 | 3/4" - 16UNF | 9,90 | 40,49 | 56 | 18,24 | 48 | 60 | 16 | 6,4 | 9 | 10,82 | M8x30 | 5/16x1"1/4 | 4075 | 0,33 |
| 414 | 1/2" | AFS401J078 | 7/8" - 14UN | 12,30 | 40,49 | 56 | 18,24 | 48 | 60 | 16 | 6,8 | 9 | 13,69 | M8x30 | 5/16x1"1/4 | 4075 | 0,40 |
| 414 | 3/4" | AFS402J | 1"1/16 - 12UN | 15,50 | 50,80 | 71 | 23,80 | 60 | 73 | 19 | 8,0 | 11,5 | 16,87 | M10x40 | 3/8x1"1/2 | 4100 | 0,68 |
| 414 | 1" | AFS403J | 1"5/16 - 12UN | 21,50 | 57,15 | 81 | 27,76 | 70 | 82 | 24 | 8,0 | 13 | 23,19 | M12x45 | 7/16x1"3/4 | 4131 | 1,03 |
| 414 | 1"1/4 | AFS404J | 1"5/8 - 12UN | 27,50 | 66,68 | 95 | 31,75 | 78 | 92 | 27 | 9,3 | 15 * | 29,13 | M14x45 | 1/2x1"3/4 | 4150 | 1,66 |
| 414 | 1"1/2 | AFS405J | 1"7/8 - 12UN | 33,00 | 79,38 | 113 | 36,50 | 95 | 96 | 30 | 9,6 | 17 | 35,08 | M16x50 | 5/8x2" | 4187 | 2,23 |

**DESIGNAZIONE PER ORDINE
DESIGNATION FOR ORDER**

Materiale / Material

ST52.3

Solo flangia
Only flange

AFS...J

Flangia completa di viti metriche, grower e o-ring
Flange complete of metric screws, grower type washers and o-ring

AFS...JM

Flangia completa di viti unc, grower e o-ring
Flange complete of unc screws, grower type washers and o-ring

AFS...JU

NOTE / NOTES

* Per viti unc L=13,5

* For unc screws L=13,5