



K4



: 24

- NC : L 26 x H 55
 - NA : L 26 x H 45

: - 20°C + 80°C

: 200 / ± 5%

20°C

~ 6%

~ 10%

: 0,06

: 10⁶ 70 20°C

: 2 48 AC

1 A 48 DC

DIN 40050: IP54 P1 ()

: 12



- K4X

AISI 316

- K4L

, EPDM, PTFE



HOW TO ORDER

K4

P1

		P														
			0	1	2	3	4	5	6							
R	0,2>2.5	25	1/8" BSP	1/4" BSP	1/8" BSPT	M10x1	1/8" NPT	1/4" NPT	1/4" BSPT	X AISI316L L OTTONE	V VITON T PTFE E EPDM NBR	D U				
S	1>12	25	1/8" BSP	1/4" BSP	1/8" BSPT	M10x1	1/8" NPT	1/4" NPT	1/4" BSPT							
SP	1>12	300	1/8" BSP	1/4" BSP	1/8" BSPT	M10x1	1/8" NPT	1/4" NPT	1/4" BSPT							
T	5>50	200	1/8" BSP	1/4" BSP	1/8" BSPT	M10x1	1/8" NPT	1/4" NPT	1/4" BSPT							
TP	5>50	300	1/8" BSP	1/4" BSP	1/8" BSPT	M10x1	1/8" NPT	1/4" NPT	1/4" BSPT							
V	10>100	300	1/8" BSP	1/4" BSP	1/8" BSPT	M10x1	1/8" NPT	1/4" NPT	1/4" BSPT							
Z	20>200	300	1/8" BSP	1/4" BSP	1/8" BSPT	M10x1	1/8" NPT	1/4" NPT	1/4" BSPT							
Y	50>400	600	1/8" BSP	1/4" BSP	1/8" BSPT	M10x1	1/8" NPT	1/4" NPT	1/4" BSPT							